

© 2013 American Foundry Society

Meets the Requirements of OSHA Standard 29 CFR 1910.1200 Hazard Communication and EPA Supplier Notification Requirements under Section 313 of the Emergency Planning and Community Right-to-Know Act. **SAFETY DATA SHEET (SDS)**

ALUMINUM CASTINGS-500 SERIES

SDS SC-000-056 Rev. 13

DATE ISSUED

10/13

SECTION 1—PRODUCT IDENTIFICATION & COMPANY INFORMATION

PRODUCT NAME

ALUMINUM CASTINGS-500 SERIES

OTHER DESIGNATIONS: ASTM (American Society for Testing & Materials) Specification No's., (ACI (Alloy Casting Institute) Alloy Designations—Grades)

None

PRODUCT IDENTIFICATION (Label Identifier)

See Above

MANUFACTURER'S NAME	STREET ADDRESS
Meloon Foundries LLC	1841 LeMoyne Ave
EMERGENCY TELEPHONE NO.	MAILING ADDRESS
315-454-3231	1841 LeMoyne Ave
TELEPHONE NO.	CITY, STATE, ZIP CODE, COUNTRY
315-454-3231	Syracuse, NY 13208, USA
FAX NO.	E-MAIL ADDRESS/WEBSITE
315-454-8559	wendy@meloon.com / www.meloon.com

RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Solid casting; no restrictions

SECTION 2—HAZARD IDENTIFICATION

CLASSIFICATION

Castings are metallic articles that do not present health hazards in their unaltered state.

OTHER HAZARDS

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds of these elements with different exposure limits than those listed above. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Section 8 for further information.

SECTION 3—COMPOSITION / INFORMATION ON INGREDIENTS CHEMICAL NAME/COMMON NAME/SYNONYM Wt % **CAS NUMBER** Aluminum (AI) Balance 7429-90-5 Chromium (Cr) < 0.25 7440-47-3 0.15-0.40 Copper (Cu) 7440-50-8 Iron (Fe) 0.1 - 1.81309-37-1 Magnesium (Mg) 0.8 - 10.61309-48-4 Manganese (Mn) 0.10 - 0.257439-96-5 0.05 - 0.40Nickel (Ni) 7440-02-0 Silicon (Si) 0.1 - 2.27440-21-3 Titanium (Ti) 0.10 - 0.257440-32-6 0.05 - 2.201314-13-2 Zinc (Zn)

SECTION 4—FIRST AID MEASURES

EYE CONTACT: Not applicable

SKIN CONTACT: No special requirements

INGESTION: Not applicable
INHALATION: Not applicable

SECTION 5—FIREFIGHTING MEASURES

FLAMMABLE PROPERTIES

Non-combustible as supplied. Small chips, fine turnings and dust from processing may be readily ignitable.

EXTINGUISHING MEDIA

Not applicable to metal castings. Use Class D extinguishing agents on fines, dust or molten metal. Use coarse water spray on chips and turnings. DO NOT USE halogenated extinguishing agents on small chips/fines.

PROTECTION OF FIREFIGHTERS: Not applicable

SECTION 6—ACCIDENTAL RELEASE MEASURES

Not applicable

SECTION 7—HANDLING & STORAGE

RECOMMENDED STORAGE

No special requirements

PROCEDURES FOR HANDLING

Proper hand and foot protection is recommended.

SECTION 8—EXPOSURE CONTROLS/ PERSONAL PROTECTION

ENGINEERING CONTROLS

None Required. There are no health hazards from these castings in solid form.

SUBSTANCE	ACGIH TLV mg/m ³	OSHA PEL mg/m ³	
Aluminum (as Al)			
Total Dust	N/E	15	
Respirable Dust	1 (R)	5	
Chromium (as Cr)	0.5	1	
Copper (as Cu)			
Fume	0.2	0.1	
Dust and Mist	1	1	
Iron (Fe)	N/E	N/E	
Magnesium (as Mg)	N/E	N/E	
Manganaga and inargania compounds (as Mn)	0.02 (R)	5 (C)	
Manganese and inorganic compounds (as Mn)	0.1 (I)	5 (C)	
Nickel (Ni)	1.5 (I)	1	
Silicon (Metal) (as Si)			
Total Dust	N/E	15	
Respirable Dust	N/E	5	
Titanium (Ti)	N/E	N/E	
Zinc (as Zn)	N/E	N/E	

SUPPLEMENTAL INFORMATION

Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.

Fumes from hot processes may contain other compounds of these elements with different exposure limits than those listed above. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Exposure limits for the most common contaminants are offered as reference. Please consult a competent person for guidance on exposure assessment and controls.

In particular, Hexavalent Chromium is an OSHA Expanded Health Standard; refer to OSHA 29 CFR 1910.1026-Chromium (VI) for complete requirements.

SUBSTANCE	ACGIH TLV mg/m ³	OSHA PEL mg/m³
Aluminum oxide	N/E	15
Total Dust	N/E	5
Respirable Dust		
Chromium Compounds (as Cr)		
Chromium (II) inorganic compounds	N/E	0.5
Chromium (III) inorganic compounds	0.5	0.5
Chromium (VI) inorganic compounds, certain water insoluble	0.01	0.005
Chromium (VI) inorganic compounds, water soluble	0.05	0.005
Chromium (VI) all forms and compounds	N/E	0.005
Iron Oxide (Fe ₂ O ₃)	5 (R)	10
Magnesium oxide	10 (I)	15
Manganese fume (as Mn)	0.2	5 (C)
Nickel compounds (as Ni)		
Nickel, Insoluble compounds	0.2 (I)	1
Nickel, Soluble compounds	0.1 (I)	1
Nickel oxide	0.2 (I)	1
Titanium dioxide (as TiO ₂)	10.0	N/E
Total dust	N/E	15
Zinc and compounds	N/E	N/E
Zinc oxide total dust	N/E	15
Zinc oxide respirable dust	2	5
Zinc oxide fume	N/E	5

TERMS

All exposure limits referenced above are 8 hour time weighted averages (TWA) unless otherwise noted.

N/E = None Established

C = Ceiling

I = Inhalable fraction

R = Respirable fraction

TLV = Threshold Limit Value/ACGIH (American Conference of Industrial Hygienists)

PEL = Permissible Exposure Limit/OSHA (Occupational Safety & Health Administration)

STEL = Short Term Exposure Limit

 $mg/m^3 = milligrams per cubic meter$

PERSONAL PROTECTION

Proper hand and foot protection is recommended.

SECTION 9—PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE

Solid, silver color

ODOR/ODOR THRESHOLD None	VAPOR DENSITY Not applicable
MELTING POINT/FREEZING POINT Approximately 488-646°C (910-1195°F)	SPECIFIC GRAVITY (relative density) 2.56–2.64 g/cm ³ for aluminum
BOILING POINT	VAPOR PRESSURE
2326°C (4220°F) for aluminum	Not applicable
FLASH POINT	EVAPORATION RATE
Not applicable for solid castings	Not applicable

FLAMMABILITY	SOLUBILITY IN WATER
Not flammable	Insoluble
UPPER AND LOWER FLAMMABILITY LIMITS	pH
Not applicable for solid castings	Not applicable
AUTO IGNITION TEMPERATURE	VISCOSITY
Not applicable	Not applicable
DECOMPOSITION TEMPERATURE	PARTITION COEFFICIENT
Not applicable	Not applicable

SECTION 10—STABILITY & REACTIVITY

CHEMICAL STABILITY

Stable as shipped

CONDITIONS TO AVOID

Not applicable to castings. Fine metal dust or powder produced by grinding or polishing aluminum metal can burn or explode and must be protected from ignition sources such as grinding sparks, etc.

REACTIVITY	INCOMPATIBLE MATERIALS
Castings are not reactive. Under some conditions metal chips, fines and dust may be incompatible with	Not applicable to castings.
water, halogenated solvents, strong oxidizers, acids	
and alkalis, and iron oxide and may ignite or explode.	
HAZARDOUS DECOMPOSITION PRODUCTS	POSSIBILITY OF HAZARDOUS REACTIONS
None	Not applicable to castings

SECTION 11—TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT: None

SKIN: None

INGESTION: None

INHALATION: None

Carcinogen Classification of Ingredients

INGREDIENT	OSHA	NTP	IARC	TARGET ORGAN
Chromium (metal)	NL	NL	3	Lung Nood
Chromium VI, (hexavalent)	Y	K	1	Lung, Nasal
Nickel, Insoluble compounds as Ni	NL	K	NL	
Nickel, Soluble compounds as Ni	NL	K	NL	Lung, Nasal
Nickel, Elemental	NL	R	2B	

TERMS

OSHA—Occupational Safety & Health Administration

Y = Listed as a Human Carcinogen

NTP—National Toxicology Program

- K = Known to be a Human Carcinogen
- R = Reasonably Anticipated to be a Human Carcinogen (RAHC)

IARC—International Agency for Research on Cancer

- 1 = Carcinogen to Humans
- 2A = Probably Carcinogenic to Humans
- 2B = Possibly Carcinogenic to Humans
- 3 = Unclassifiable as to Carcinogenicity in Humans
- 4 = Probably not Carcinogenic to Humans

Other

NL = Not Listed

SECTION 12—ECOLOGICAL INFORMATION		
ECOTOXICITY	PERSISTENCE AND DEGRADABILITY	
Not applicable	Not applicable	
BIOACCUMULATION POTENTIAL	MOBILITY IN SOIL	
Not applicable	Not applicable	

OTHER ADVERSE EFFECTS

Not applicable

SECTION 13—DISPOSAL CONSIDERATIONS

Recover or recycle if possible. Dispose of according to federal, state and local regulations. Dust collected from machining, welding, etc. may be classified as a hazardous waste. Consult federal, state and local regulations.

SECTION 14—TRANSPORT INFORMATION		
US DEPARTMENT OF TRANSPORTATION (DOT)-HMR	CANADIAN TRANSPORTATION OF DANGEROUS GOODS (TDG)	
Not Regulated	Not regulated	
UN SHIPPING NAME	UN NUMBER	
Not regulated	Not regulated	
TRANSPORT HAZARD CLASS	PACKING GROUP	
Not regulated	Not regulated	
ENVIRONMENTAL HAZARDS	LABEL(S) REQUIRED?	
None	No	
TRANSPORT IN BULK	SPECIAL SHIPPING INFORMATION	
Not applicable	Not applicable	

SECTION 15—REGULATORY INFORMATION

USA-OSHA (Hazard Communication Standard)

Reference 29 CFR 1910.1200 and 1910.1000. A finished casting is an article as defined in the OSHA Hazard Communication Standard 29CFR 1910.1200 (c). Dust or fumes generated by cleaning, machining, grinding, or welding of the casting may produce airborne contaminants, such as aluminum dust, aluminum oxide, chromium, copper, iron, magnesium oxide, manganese, nickel, silicon, titanium dioxide, zinc oxide and silica. For chromium references see 29 CFR 1910.1026.

USA-EPA (Toxic Substances Control Act-TSCA)

All components of these products are on the TSCA inventory list or are excluded from listing.

USA-EPA (SARA Title III)

Releases to the environment of Chromium, Copper, Manganese, Nickel and Aluminum (dust or fume only), may be subject to reporting under Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

CANADA-WHMIS (Workplace Hazardous Materials Information System)

This SDS has been prepared according to the hazard criteria of the Controlled Product Regulations (CPR) and the SDS contains the information required by the CPR.

CANADIAN DSL (Domestic Substance List) Inventory Status

All components of these products are on the DSL Inventory.

CEPA (Canadian Environmental Protection Act)

Chromium and nickel are on the CEPA Priorities Substances Lists.

EINECS No. (European Inventory of Existing Commercial Chemical Substances)

All components of these products are on the EINECS list.

RoHS (Restriction of Certain Hazardous Substances) Compliance

Castings comply with RoHS

CALIFORNIA PROPOSITION 65 Compliance

WARNING: This product contains or produces chemicals known to the State of California to cause cancer and birth defects (or other reproductive harm). (California Health & Safety Code 25248.5 et seq.)

U.S. STATE REGULATORY INFORMATION

Some of the components listed in Section 3 may be covered under specific state regulations.

SECTION 16—OTHER INFORMATION		
SDS SHEET PREPARED BY	DATE	
American Foundry Society, Inc.	10/13	
Occupational Safety & Health Committee (10-Q)		

NOTE

This data and label information is offered in good faith as typical values and not as a product specification. No warranty either expressed or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review the recommendations in specific context of the intended use and determine if they are appropriate.

Addendum: Label Information

PRODUCT IDENTIFIER

SC-000-056 Rev. 13 ALUMINUM CASTINGS-500 SERIES

SUPPLIER IDENTIFICATION	HAZARD PICTOGRAMS
Company Name Meloon Foundries LLC	None*
Street Address 1841 LeMoyne Ave	
Mailing Address 1841 LeMoyne Ave	SIGNAL WORD
City Syracuse State NY	None*
Zip/Postal Code 13208 Country USA	
Emergency Phone Number 315-454-3231	
Other Info	
PRECAUTIONARY STATEMENTS	HAZARD STATEMENTS
None*	None*

OTHER INFORMATION

- 1. Grinding castings that have not been cleaned or that contain embedded sand may generate significant amounts of dust containing crystalline silica.
- 2. Fumes from hot processes may contain other compounds with different exposure limits. Dust or fumes generated by machining, grinding, welding or thermal cutting of the casting may produce airborne contaminants. Consult Sections 3 & 8 of the SDS for further information.

^{*}Castings do not present hazards in their original form.